



SUNELL 2MP/5MP DVR price list



اسفند ماه ۱۴۰۲

Model	SN-ADR3304E1	SN-ADR3804E1	SN-ADR3808E1	SN-ADR3316E1	SN-ADR3316E2	SN-ADR3816E2
	DVR4H (Hisilicon Chip)	DVR4HG	DVR8HG	DVR16H (Hisilicon Chip)	DVR16HH (Hisilicon Chip)	DVR16HF
picture						
Video and Audio						
Analog Camera Input	4ch BNC		8ch BNC	16ch BNC		
AHD/TVI/CVI Camera	5MP/4MP/3MP/1080P720P @25/30fps					
CVBS Camera	PAL/NTSC					
IP Camera Input	4+2 each channel up to 1080P		8+4, each channel up to 5MP	16ch, each channel up to 1080P		16ch each channel up to 5MP
Audio In/Out	1ch input, 1ch output, RCA			6ch input, 1ch output, RCA		
Two-way Talk	N/A					
Display						
Interface	1ch HD-OUT, 1ch VGA					
Resolution	HD-OUT: 3840x2160, 1920x1080, 1280x1024, 1440x900 VGA: 1920x1080, 1280x1024, 1440x900 & CVBS Output					
Multi-screen Display	1/4/9			1/4/9/16		
Recording						
Compression	H.265 / H.264					
Resolution	5MP-N, 4MP-N, 1080P, 720P, 960H, D1, CIF					
Record Rate	5MP-N@10fps, 4M@7fps, 1080P @15fps	4K-N@7fps, 5MP@6fps, 4MP@7fps, 1080P@15fps	4K-N@8fps, 5MP@7fps, 4MP@8fps, 1080P@15fps	5MP-N@10fps, 4MP-N@15fps, 1080P@15fps	4K-N@8fps, 5MP@7fps, 4MP@8fps, 1080P@15fps	
Bit Rate	16Kbps~4096Kbps					
Record Mode	Manual, Event, Timer					
Record Interval	Post-record: 30 – 60 sec					
Video Detection and Alarm						
Trigger Events	Recording, Buzzer, Push message, Pop up message					
Video Detection	Motion Detection, Video Loss, Camera Tamper					
Alarm input	N/A			4/1		
Network						
Interface	1 RJ-45 port (10/100Mbps)					
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP					
Max. User Access	Access 4 users					
Smart Phone	iPhone, iPad, Android					
Interoperability	ONVIF, SDK, CGI					
Playback and Backup						
Playback	4,1		9,4,1	16,9,4,1		
Search Mode	Time /Date, Alarm, Picture grid, Event					
Playback Function	Play, Pause, Stop, Next Frame, Fast play, Slow Play, Layout, Shuffle, Backup Selection, Digital Zoom					
Storage						
Internal HDD	1 SATA Ports, up to 8TB for each HDD			2 SATA Ports, up to 8TB for each HDD		
eSATA	N/A					
Interface						
USB	2 ports (USB 2.0 x2)					
RS232	N/A					
RS485	N/A			1 Port, for PTZ Control		
General						
Power Supply	DC12V/2A			DC12V/4A		
Power Consumption	Max 10W (without HDD)	Max 15W (without HDD)		Max 10W (without HDD)		Max 15W (without HDD)
Operating Temperature	-10 °C ~ 50 °C (14 °F ~ 122 °F)					
Dimensions (mm)	255(L) x 244(W) x 44(H)			350(L) x 305(W) x 49(H)		
Net Weight	900 g	700 g	1 Kg	1 Kg	1.8 Kg	