


	32 Ch 2HDD NVR
Model	SN-NVR2532E2 (NVR32LN)
Picture	
Audio and Video	
IP Camera Input	32 Channel
Audio I/O	1/1, RCA
Two-way Talk	1ch input, 1ch output
Display	
Interface	1 HDMI, 1 VGA
Resolution	HDMI: 1920×1080,1440×900,1280×1024
	VGA: 1920×1080, 1280×1024, 1280×720
Decoding Capacity	1ch 8MP/4ch 1080P@30fps
Multi-screen Display	1/4/9/16/32
Recording	
Compression	H.265+ / H.265/H.264+/H.264
Resolution	8MP/6MP/5MP/4MP/3MP/1080P/720P/ D1&etc.
Record Rate	160 Mbps
Record Mode	Manual, Schedule (Regular, Continuous), Motion Detection, Video Loss, Camera Tamper, Alarm in
Record Interval	Post-record: 30 ~ 60 sec
Video Detection and Alarm	
Trigger Events	Recording, Buzzer, Push message, Pop up message.
Video Detection	Motion Detection, Video Loss, Camera Tamper
Alarm In/Out	8/2
Playback and Backup	
Sync Playback	32/16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device
Network	
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP
Max. User	Access 9 users
Interoperability	ONVIF 2.4, SDK, CGI
Storage	
Internal HDD	2 SATA Ports up to 8TB for each HDD
eSATA	N/A
Interface	
USB	2 ports (USB 2.0 x2)
Interface	2 RJ-45 port (10/100/1000Mbps)
PoE Interface	N/A
PoE Max Power	N/A
Reset Button	
General	
Power Supply	DC12V/3A
Power Consumption	< 15W (without HDD)
Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Dimensions	372×310.5×46.5mm
Net Weight	3kg (No disk)



32ch Raid NVR price list p2/2



اسفند ماه ۱۴۰۲

Model	SN-NVR2632E4 (NVR32MN)	SN-NVR3632E8 (NVR32FN)
Picture		
Video Input		
IP Camera Input	32 Channel	
Incoming Bandwidth	320Mbps	
Outgoing Bandwidth	320Mbps	
Video Output		
HDMI Output	HDMI 1: 1920x1080,1440x900, 1280x1024	
	HDMI 2: 3840x2160,1920x1080, 1440x900, 1280x1024	
VGA Output	1920x1080,1440x900,1280x1024	
Different Source Output	Support	
Decoding Capacity	1ch 12MP, 4ch 8MP, 8ch 4MP, 16ch 1080P, 32ch 720P	
Dual Stream	Support	
Multi-screen Display	1st Screen: 1/4/8/9/16/32/36	
	2nd Screen: 1/4/8/9/16	
Recording		
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.	
Recording Mode	Manual, Schedule (Regular, Continuous), Event	
Trigger Events	Motion Detection, Video Loss, Alarm in	Motion Detection, Video Loss, Alarm in, IVS
Playback and Backup		
Sync Playback	16/9/4/1	
Search Mode	Time /Date, Alarm, Picture grid, Event	
Backup Mode	USB Device, Network, eSATA	
Network		
Interface	2 RJ-45 port (10/100/1000Mbps)	
PoE	N/A	
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE	
Remote Users	8 users	
Smart Phone	iPhone, iPad, Android	
Interoperability	ONVIF, SDK	
Storage		
HDD	4 SATA Ports, up to 12TB for each HDD	8 SATA Ports, up to 12TB for each HDD
eSATA	1 eSATA Port	
Cloud Storage	Support	
Disk Array		
Array Type	RAID 5, RAID 6, RAID 10	
Interface		
Audio I/O	1/1	
Alarm Input	16ch	
Alarm Output	4ch	
USB	3 ports (USB 2.0 x 2, USB3.0 x 1)	
RS485	1 Port	
RS232	1 Port	
General		
Power Supply	AC100 ~ 240V	
Power Consumption	< 15W (without HDD)	
Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)	
Storage Conditions	Less than 90% RH	
Dimensions	440 x 368.3 x 70mm	440 x 433.5 x 93mm
Net Weight	4.5kg (without HDD)	7.2kg (without HDD)