

**4K SUNELL DVR**

اسفند ماه ۱۴۰۲



Model	SN-ADR3604E1 (DVR4H5)	SN-ADR3908E1 (DVR8K4)	SN-ADR3608E1 (DVR8H5)	SN-ADR3916E2 (DVR16K4)
picture				
<b>Video and Audio</b>				
Analog Camera Input	4ch BNC	8ch BNC		16ch BNC
AHD/TVI/CVI Camera	4K/5MP/4MP/3MP/1080P/720P @25/30fps			
CVBS Camera	PAL/NTSC			
IP Camera Input	4ch each channel up to 1080P	8ch each channel up to 5MP	8ch each channel up to 1080P	16ch each channel up to 8MP
Audio In/Out	4ch input, 1ch output, RCA			
<b>Display</b>				
Interface	1ch HD-OUT, 1ch VGA, 1ch CVBS			
Resolution	HD-OUT: 3840x2160, 1920x1080, 1280x1024, 1440x900			
	VGA: 1920x1080, 1280x1024, 1440x900			
Multi-screen Display	1/4	1/4/8		1/4/9/16
<b>Recording</b>				
Compression	H.265 / H.264			
Resolution	4K, 5MP, 4MP, 1080P, 720P, 960H, D1, CIF			
Record Rate	4K@8fps, 5MP@15fps, 1080P@30fps	4K@7fps, 5MP@12fps, 4MP@15fps, 1080P@30fps	4K@8fps, 5MP@15fps, 1080P@30fps	4K@7fps, 5MP@12fps, 4MP@15fps, 1080P@30fps
Bit Rate	128Kbps~6144Kbps			
Record Mode	Manual, Event, Timer			
Record Interval	Post-record: 30 ~ 60 sec			
<b>Video Detection and Alarm</b>				
Trigger Events	Recording, Buzzer, Push message, Pop up message			
Video Detection	Motion Detection, Video Loss, Camera Tamper			
Alarm in/out	N/A			8/1
<b>Network</b>				
Interface	1 RJ-45 port (10/100Mbps)			
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP			
Max. User Access	Access 4 users			
Smart Phone	iPhone, iPad, Android			
Interoperability	ONVIF, SDK, CGI			
<b>Playback and Backup</b>				
Playback	4/1	8/4/1		16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event			
Playback Function	Play, Pause, Stop, Next Frame, Fast play, Slow Play, Layout, Shuffle, Backup Selection, Digital Zoom			
Backup Mode	USB HDD			
<b>Storage</b>				
Internal HDD	1 SATA Ports up to 8TB for each HDD			2 SATA Ports up to 8TB for each HDD
eSATA	N/A			
<b>Interface</b>				
USB	2 ports (USB 2.0 x2)			
RS485	1 Port, for PTZ Control			
<b>General</b>				
Power Supply	DC12V/2A			DC12V/4A
Power Consumption	Max 5W (without HDD)	Max 10W (without HDD)		Max 15W (without HDD)
Operating Temperature	-10 °C ~ 50 °C (14 °F ~ 122 °F)			
Storage Conditions	Less than 90% RH			
Dimensions(mm)	255(L) x 244(W) x 44(H)	255(L) x 225(W) x 44(H)	255(L) x 244(W) x 44(H)	350(L) x 305(W) x 49(H)
Net Weight	900g	750g	1Kg	1.8Kg